



| No. | PLATING                    |
|-----|----------------------------|
| 01  | Brass gold 1u"             |
| 02  | Brass gold 3 u"            |
| 03  | Brass gold 5 u"            |
| 04  | Brass gold 10 u"           |
| 05  | Brass gold 15 u"           |
| 06  | Brass gold 30 u"           |
| 07  | Phosphor bronze gold 1u"   |
| 08  | Phosphor bronze gold 3 u"  |
| 09  | Phosphor bronze gold 5 u"  |
| 10  | Phosphor bronze gold 10 u" |
| 11  | Phosphor bronze gold 15 u" |
| 12  | Phosphor bronze gold 30 u" |

| Position | Dimension |       |
|----------|-----------|-------|
|          | A         | B     |
| 14 P     | 22.30     | 18.60 |
| 16 P     | 24.80     | 21.20 |
| 20 P     | 29.90     | 26.20 |
| 24 P     | 34.90     | 31.40 |
| 34 P     | 47.70     | 43.90 |
| 40 P     | 55.60     | 51.90 |
| 50 P     | 68.40     | 64.70 |

| NO. | Feature Depiction   |
|-----|---|
| 201 | (Y2)Have ear  |
| 202 | (N2)without ear   |
| 203 | (Y2)Have ear,middle cover print"UL"                                     |
| 205 | (Y2)Have ear,middle cover print"FC-**P"                                 |
| 222 | (N2)Without ear,black,plug up the 20th pin                              |
| 224 | (Y2)have ear,plug up 20th pin,housing print"tyco"                       |
| 225 | (Y2)have ear,housing print"tyco"  |
| 226 | (Y2)have ear,plug up 20th pin,middle cover print"UL"                    |
| 246 | (Y2)blue 401N,take out the 20th contact                                 |
| 247 | (Y2)gray 802N,take out the 20th contact                                 |
| 250 | (Y2)gray ,plug up 20th pin,take out 28th contact,middle cover print"UL" |
| 351 | (Y3)Have ear,black  |
| 352 | (N3)without ear,black   |
| 356 | (Y3)Have ear,gray 802N  |
| 357 | (Y3)Have ear,black,housing print"tyco"                                  |
| 358 | (N3)withot ear,gray 802N  |
| 360 | (Y3)Have ear,black,housing print"KEENTOP"                               |
| 364 | (Y3)without ear,black,middle cover print"UL"                            |
| 382 | (Y3)Have ear,plug up the 3th pin,middle print"UL"                       |
| 383 | (Y3)Have ear,plug up the 5th pin,middle print"UL"                       |

- Note:
- <1>.Plastic material :PBT+G/F,UL 94V-0.
  - <2>.Contacts: copper alloy.
  - <3>.Plating: 30-50 u" nickel plating under,au plated on gold plating area ,see table.
  - <4>.External must be non-damage non-fading
  - <5>.The"@ "dimension must by QC.
  - <6>.Operating temperature:-20°C~85°C.
  - <7>.Current Rating:1.5 Amp.
  - <8>.Insulation resistance:1000 MΩ Min.
  - <9>.Dielectric voltage: 300V AC for 1 minute.
  - <10>.Product Number :

