



FEATURES:

PBT+30% Glass Fiber [UL 94V-0]
 Low Profile header body helps maximum packaging density
 Available with warp post tail header
 Fully-shrouded body provides maximum
 Protection for header mating pins

SPECIFICATIONS:

Current rating: 2A AC. DC.
 Voltage rating: 250V AC. Maximum
 Temperature range: Initial Value/10mΩ max.
 After environmental testing
 /20mΩ max.
 Insulation resistance: 5000 M min.
 Withstand Voltage: 1500V AC/minute

Ordering Information 809MS Series

Series no.	NO. Of contacts	Configuration	Material	Color	Contact Plating	Uninstall Contacts NO.	ROSH
809MS	30P	00	C	01	C01	U00	L
809MS Series	8P 10P 12P 14P 16P 20P 22P 24P 26P 30P 32P 34P 36P 40P 44P 50P 60P 64P	00: 180° 01: 90°	A: NYLON 6T B: NYLON 66 C: PBT	00: BLACK 01: WHITE 02: BLUE 03: NATURE	C00: TIN C01: GOLD FLASH C02: 5u" GOLD C03: 10u" GOLD C04: 15u" GOLD C05: 30u" GOLD	U00: FULL PIN U01: Uninstall PIN#1 : : : U29: Uninstall PIN#29 U29: Uninstall PIN#30	L=Pb Free Plating Product