



Position	Dimention		Position	Dimention	
	A	B		A	B
10	8.00	14.30	28	26.00	32.30
12	10.00	16.30	30	28.00	34.30
14	12.00	18.30	34	32.00	38.30
16	14.00	20.30	40	38.00	44.30
20	18.00	24.30	44	42.00	48.30
24	22.00	28.30	50	48.00	54.30

Note:

- <1>.Plastic material :PBT&DR-48,Black&Grey.
- <2>.Contact: copper alloy.
- <3>.Plating: 30-50 u" nickel plating under,au plated on gold plating area ,see table.
- <4>.External must be non-damage non-fading
- <5>.The"@ "dimension must by QC.
- <6>.Operating temperature:-20°C~105°C.
- <7>.Current Rating:1.0 Amp.
- <8>.Insulation resistance:1000 MΩ Min.
- <9>.Dielectric voltage: 300V AC for 1 minute.
- <10>.Product Number :

PIN Number A05 ** ** ** ** **

- 00:PBT +G/F
- 13:DR-48
- 01 Brass bronze plated gold 1U"
- 05 Brass bronze plated gold 15U"
- 06 Brass bronze plated gold 30U"
- 07 Phosphor bronze plated gold 1U"
- 11 Phosphor bronze plated gold 15U"
- 13 Brass bronze plated tin (no-Pb)
- 15 Phosphor bronze plated tin (no-Pb)
- 01:RoHS
- 02:SONY
- 801:Housing and Contact
- 851:Housing and Contact and Cover
- 855:Grey 802N